


ENGINE

Engine Version	FUSO 4P10-T4 diesel
Configuration	4 Cyl. In-line DOHC, 4-valve
Туре	Variable geometry turbo charged with intercooler
Displacement	3 litre (2,998cc)
Power (DIN)	110kW @ 2840~3500rpm
Torque (DIN)	370Nm @ 1350~2840rpm
Max Engine Speed (rpm)	4100
Air Cleaner	Restrictor indicator + vertical intake on RH side
Emission Control	Diesel particulate filter with status dash display
Emission Level	EURO 5 (ADR 80/03) EEV-rated (Enhanced Environmentally-Friendly Vehicle)

4P10-T4



TRANSMISSION AND CLUTCH

Туре	6-spd DUONIC AMT	5-spd Manual
Version	FUSO DUONIC M038S6	FUSO M038S5
Features	Auto/Manual modes + fuel-saving Eco Mode, virtually instant gear shifts	In-dash gear lever
Ratios	1st: 5.397 2nd: 3.788 3rd: 2.310 4th: 1.474 5th: 1.000 6th: 0.701 Rev: 5.397	1st: 5.494 2nd: 3.193 3rd: 1.689 4th: 1.000 5th: 0.723 Rev: 5.494
Clutch	DUONIC wet multi-plate dual clutch (no pedal)	FUSO C4W30 direct hydraulic single dry plate
PTO Opening	LH side	LH side

KERB WEIGHTS AND MAX AXLE LOADS (KG)

		Vehicle Ratings*		TMUB**	Max Axle	Loadings*	Ke	erb Weights*	**
Model Type	Model Code	GVM [†]	GCM [†]	Total	Front	Rear	Front	Rear	Total
4x2 816G Wide Cab 6-spd DUO	FEB71GR3SFBG	7,500	11,000	750	3,100	6,000	1,610	835	2,445
4x2 816G Wide Cab 5-spd MAN	FEB71GR4SFBG	7,500	11,000	750	3,100	6,000	1,595	830	2,425

* Vehicle ratings and max axle loadings may be limited by local regulations. ** Tow mass unbraked. *** Includes 10L fuel and spare wheel; subject to 2.5% variation (+/-) ⁺ Class 1 options available (5,995kg GVM / 9,500kg GCM)

ACTIVE SAFETY FEATURES	CAB & CHASSIS SAFETY FEATURES	
ABS + Electronic Brake Force Distribution (EBD)	ECE R-29 Reinforced Cab + Side Intrusion bars	Hill Start Assist (Adjustable)
Active Emergency Braking System (AEBS)	Driver Steering Wheel Airbag	Heated Rearview Mirrors
Anti-Slip Regulator (ASR)	Passenger Dashboard Airbag	Brake Wear Indicator
Electronic Stability Control (ESC)	Speed Limiter (Adjustable)	4-Wheel Disc Brakes
Lane Departure Warning System (LDWS)	Cruise Control (DUO)	
Brake Priority System		



FUEL	
Injection System	Bosch common rail direct injection Bosch piezo technology injectors
Tank Type	100L steel tank with locking cap
Filtration	Filter with water separator and indicator sensor

ELECTRICAL	
Voltage / Alternator	12V negative earth / 110 amp
Battery	Heavy duty 115D31L x 2
Head & Fog lamps	LED

AXLE / SUSP. / BRAKES

Front Axie	FUSU F3501 I-beam
Rear Axle	FUSO D035H full floating banjo type 5.714:1 (DUO) 5.285:1 (MAN)
Max Operating Capacity (kg)	3,100 (front) 6,000 (rear)
Suspension	Taper-leaf (front) + multi-leaf (rear) + stabiliser bar + double-acting shock absorbers
Brakes	Hydraulic dual circuit + front and rear twin caliper discs
Park Brake	Transmission-mounted
Brake Systems	ABS + EBD + EBS + exhaust brake Brake Priority System

WHEELS AND TYRES		
Wheel Size	17.5 x 6.0-127	
Tyres	215/75R17.5	
Spare Tyre	Yes	

INSTRUMENTS		
Gauges	Speedometer with odometer, tachometer, fuel level, water temperature	
Colour Information Display	Fuel consumption, DPF bar chart from 1~9 Water temperature, maintenance reminder system, date and time, tripmeters	

OPTIONS

† Additional Cameras (up to 6)	
Truck Specific GPS Navigation	
Reversing Sensors	
Tyre Pressure Monitoring Syste	

CAB FEATURES	
Cab Type	All steel forward control fixed cab
Mounting	Hydroelastic 4 point
Interior	Fully trimmed cab with vinyl floor covering
Steering Wheel	Energy-absorbing adjustable (height and reach)
Seats (3)	Heavy-duty driver's seat with arm rest and adjustable lumbar support + passenger bench + ELR 3-point seatbelts (height-adjustable + pre- tensioner for driver) + lap belt (centre passenger)
Storage	Dual overhead storage pockets, in-dash centre document storage, door storage pockets, lockable glove box
Doors / Windows	Keyless central locking / electric windows
Temp. Control	Air conditioner / heater / demister
Accessory Power	12V accessory power outlet / cigar lighter
Fuso FS8000 8" Multimedia Touchscreen Unit	AM/FM/DAB + USB + AUX Apple Carplay and Android Auto Wi-Fi enabled for internet radio Bluetooth; 64GB capacity storage; HD reverse camera included [†]

PERFORM	ANCE		
Turning Circle (kerb to kerb - metres)		13.6	
Road Speed (km/h) at Max Engine Speed		127	
Engine Speed (rpm) at 90km/hr (top gear)		2535 (DUO) 2420 (MAN)	
Gradeability at Rated GVM (theoretical)*		34%	
Notes		*This is theoretical performance only. Actual performance may vary under different conditions	

DIMENSIONS (MM)	
Wheelbase	3,850
Overall Length / Height / Width	6,685 / 2,185 / 2,030
Width Rear Axle	2,030
Width Front / Rear Track	1,675 / 1,560
Width Frame	750
Height Frame at Rear Axle	797

CHASSIS	
Ladder Frame	192 x 60 x 6 (mm)
Tensile Strength	440MPa
	noo on unuu fuoo oo na hoforo mounting

Refer to the bodybuilders guidelines on www.fuso.co.nz before mounting a body or modifying the chassis

SERVICE INTERVALS / EXTENDED WARRANTY

30,000km/12mths full service intervals (depending on application). 15,000km/6mths safety inspection with greasing (to maintain warranty cover and optimum performance).

5yrs / 200,000km warranty (3yrs / 100,000km + 2yrs / 100,000km) Have your vehicle serviced at an authorised FUSO Service Centre at the recommended servicing intervals for extended cover! Terms & conditions apply. Scan the QR code for full warranty details.



A policy of continual improvement means that specifications detailed in this brochure are subject to change without notice. Contact your authorised Fuso dealer to confirm current specifications. Fuso is a registered trademark of Mitsubishi Fuso Truck & Bus Corporation. Copyright © Fuso NZ (2024)

